

BUSHNELL TOUR 1500, 1600, 1M, PRO X7 AND MEDALIST INSTRUCTIONS

Method 1 (original):

Using the enclosed belt clip tab/screw assembly, simply screw it into the ¼ X 20 tripod mount on your rangefinder. Hand tightening should be all that is needed but if you need to tighten a little more (be careful not to overtighten) use a screwdriver or even a dime. Occasionally check to be sure the belt clip tab/screw is secure. Now just place your Quick Clip on the steel window/roof frame of your cart, and put the belt clip tab in the hole and slide down. You're good to go!

Method 2 (a better alternative):

We've drawn a white circle on the optimal spot at the laser lens end on a Bushnell 1500 Pinseeker where you would need to place our belt clip tab/3M adhesive disk assembly. You would do the same for any of the other Bushnell Lasers listed above as well as many other brands and models of laser rangefinders. This spot is where you need to carefully place the belt clip tab/3M adhesive disk assembly (see 2nd page picture) for the optimal center of gravity. With your Quick Clip, we include 3 (two spares) of these belt clip tab/3M adhesive disk assemblies, extra alcohol cleaning pads and extra 3M adhesive disks.

Using the included alcohol cleaning pad, clean the spot on your Bushnell and allow to dry. This removes any oils, sweat, grease and other yucky stuff so the adhesion is optimized. Peel the paper backing off of one of the belt clip tab/3M adhesive disk assemblies. Carefully place the belt clip tab on the black oval as shown in the picture. CAUTION: The belt clip tab/3M adhesive will want to stick immediately to whatever it touches so use care when placing it on the spot and try not to touch the adhesive with your fingers. Apply some pressure on the belt clip tab for about 30 seconds. **VERY IMPORTANT: If you follow the directions "to the letter", it will stick instantly and you won't be able to remove it using your fingers/hands (you may draw blood). It certainly cannot come off during your everyday use on the golf cart.**

Allow it to "set" for 48 to 72 before using your laser on the Quick Clip. That will enhance the adhesive properties of the 3M adhesive disk. If you follow the directions very carefully, the belt clip tab will not come off in your everyday use while playing golf. If you ever need to remove the belt clip tab, simply warm the adhesive with a hair dryer. The adhesive will soften and you can peel off the belt clip tab, though it still won't be easy. Don't try to re-use that 3M adhesive that you peeled off as it loses some of its adhesiveness. Remove it and use a fresh adhesive disk. You can re-use the belt clip tab. Remove any remaining adhesive and clean it with an alcohol pad or a clean cloth with a dab of isopropyl (rubbing) alcohol. Carefully (see CAUTION above) place the fresh 3M adhesive disk on the belt clip tab.

If you have any doubts at all about the strength, flexibility and holding power of the 3M VHB adhesive, please click on the link below. If you have any trouble opening it, simply right-click directly on the link then click on "Open Hyperlink". Or you can also copy the link and paste it into your web browser address line:

https://www.3m.com/3M/en_US/company-us/all-3m-products/~/3M-VHB-Tape-4991?N=5002385+3293223574&rt=rud



If you need more belt clip tabs or 3M adhesive disks, call us at 843-333-7453 or e-mail mike@gpsquickclip.com. Thanks for buying our Quick Clip everyone!

Michael D Owens
Phone: 843-333-7453
Fax: 843-235-8405

Email: mike@gpsquickclip.com
Web: www.gpsquickclip.com