

BUSHNELL TOUR V3 INSTRUCTIONS (Also applicable to the Tour V2)

Method 1

Using your Bushnell V3 with our GPS Quick Clip is a “no brainer”. As you know, your V3 includes a standard 1/4” threaded tripod socket. Each Quick Clip comes with 2 (one for a spare) belt clip tab/tripod socket screw assemblies. You simply screw the belt clip tab into the tripod socket (hand tight will be sufficient) of your V3. Then place the Quick Clip anywhere on the windshield/roof support frame of the golf cart. Lastly, slide the belt clip tab (that is now attached to your V3) into the keyhole slot of the Quick Clip. It’s that simple! **Be sure to check** that the belt clip tab/tripod socket screw assembly is snug in the tripod socket before and during your play.

The single magnet Quick Clip is all you need for the V3. The magnet on it has a magnetic attraction of 85 pounds so it can’t dislodge from the cart frame. That said though, if you drive the cart recklessly and/or hit a severe bump at high speed, it is possible for the V3 (or any rangefinder for that matter) to pop out of the keyhole slot.

Method 2 (a better alternative):

We’ve drawn black oval (see pictures below) on the optimal spot at the **laser lens end** on a Bushnell V3 (or V2) where you would need to place our belt clip tab/3M adhesive disk assembly. You would do the same for any of the other Bushnell Lasers as well as many other brands and models of laser rangefinders. This spot is where you need to carefully place the belt clip tab/3M adhesive disk assembly (see 2nd page picture) for the optimal center of gravity. With your Quick Clip, we include 3 (two spares) of these belt clip tab/3M adhesive disk assemblies, extra alcohol cleaning pads and extra 3M adhesive disks.

Using the included alcohol cleaning pad, clean the spot on your Bushnell and allow to dry. This removes any oils, sweat, grease and other yucky stuff so the adhesion is optimized. Peel the paper backing off of one of the belt clip tab/3M adhesive disk assemblies. Carefully place the belt clip tab on the black oval as shown in the picture. CAUTION: The belt clip tab/3M adhesive will want to stick immediately to whatever it touches so use care when placing it on the spot and try not to touch the adhesive with your fingers. Apply some pressure on the belt clip tab for about 30 seconds.

Allow it to “set” for 48 to 72 before using your laser on the Quick Clip. That will enhance the adhesive properties of the 3M adhesive disk. **IMPORTANT NOTE**: **If you follow the directions “to the letter”, it will stick instantly and you won’t be able to remove it using your fingers/hands (you may draw blood). It certainly cannot come off during your everyday use on the golf cart.** If you ever need to remove the belt clip tab, simply warm the adhesive with a hair dryer. The adhesive will soften and you can peel off the belt clip tab, though it still won’t be easy. Don’t try to re-use that 3M adhesive that you peeled off as it loses some of its adhesiveness. Remove it and use a fresh adhesive disk. You can re-use the belt clip tab. Remove any remaining adhesive and clean it with an alcohol pad or a clean cloth with a dab of isopropyl (rubbing) alcohol. Carefully (see CAUTION above) place the fresh 3M adhesive disk on the belt clip tab. If you need more of the belt clip tab/3M adhesive disk assemblies, call (843-333-7453 or email (mike@gpsquickclip.com) us. Thanks for using our Quick Clip. Mike Owens. GPS Quick Clip Inc.



